



Frank Bacon Machinery Sales Company, Inc.

4433 East Eight Mile Road • Warren, MI 48090-0886 • (586) 756-4280 • Fax (586) 756-8009 • Toll Free (800) 394-4280 •

e-mail: sales@frankbacon.com • On The Web: www.frankbacon.com

Stock #: 12235-01

We offer for your consideration, subject to prior sale and conditions stated at the left for immediate acceptance.

Conditions of Sale	Description
<p>TERMS: 30% Deposit with the order, balance before shipment.</p> <p>We reserve the right to correct typographical errors.</p> <p>GUARANTEE: Unless otherwise specified, every machine is offered with the standard MDNA (MACHINERY DEALERS NATIONAL ASSOCIATION) Return privilege to ensure your complete satisfaction. If the machine is unsatisfactory it may be returned to our warehouse, freight prepaid and in the original condition within 30 Days of shipment for a full refund less the cost of SPECIALIZED EQUIPMENT, NEW ITEMS AND RE-CERTIFICATION COSTS, When applicable.</p> <p>Care is taken to provide accurate specifications. However, Critical areas should be verified by Inspection.</p> <p>WARRANTY: FBMS Provides a ONE Year parts and labor Warranty on all reconditioned Testers and 90 Days on Reconditioned tools less all travel and/or Shipping Related Expenses. Unless otherwise specified.</p> <p style="text-align: center;">MDNA AMDA MMA ASTM SAE ASM</p>	<p>(1) USED 1.5M Capacity MTS, Four Column Fatigue Testing Load Frame.</p> <p style="text-align: center;"><u>LOAD FRAME SPECIFICATIONS:</u></p> <p>Model Number / Serial Number: T 1501, C 2264 Capacity (KIP): 4 Number Of Columns: 48" Distance Between Columns: 75" x 57" x 18" Table Size (WxDxThickness): 12' 10" (154") Maximum distance between table and crosshead: 10' Maximum distance between load cell and actuator: 100" x 75" x 23' 9" Approximate Overall Dimensions (WxDxH): 77,000 Approximate Weight (Lbs):</p> <p style="text-align: center;"><u>EQUIPPED WITH:</u></p> <ul style="list-style-type: none"> • Hydraulic Crosshead Lifts, Locks & Controls • MTS 1501KIP(tension) 2,264KIP(compression), 3000 PSI Actuator, Model 209.69, S/N 127, with 6" Stroke, LVDT • Three Stage MOOG Model 256.09 90 GPM Servo Valve, S/N 522 • Moog Model 252.21C-01 1 GPM Servo Valve, (Model 760C260A, S/N 745) • 1501 KIP MTS Fatigue Rated Axial Load Cell • MTS Model 290.22 3,000 PSI, 100 GPM Hydraulic Service Manifold S/N 152 • MTS Model 506.61 70 GPM Hydraulic Supply, S/N 210 • Thermotron Model F-54-CH-LN2 Chamber, S/N 21-9623 <p style="text-align: center;">FOB Detroit, MI</p>



Frank Bacon Machinery Sales Company, Inc.

4433 East Eight Mile Road • Warren, MI 48090-0886 • (586) 756-4280 • Fax (586) 756-8009 • Toll Free (800) 394-4280 •

e-mail: sales@frankbacon.com • On The Web: www.frankbacon.com

Stock #: 12235--02

We offer for your consideration, subject to prior sale and conditions stated at the left for immediate acceptance.

Conditions of Sale

Description

TERMS:

30% Deposit with the order, balance before shipment.

We reserve the right to correct typographical errors.

GUARANTEE:

Unless otherwise specified, every machine is offered with the standard **MDNA** (MACHINERY DEALERS NATIONAL ASSOCIATION) Return privilege to ensure your complete satisfaction. If the machine is unsatisfactory it may be returned to our warehouse, freight prepaid and in the original condition within 30 Days of shipment for a full refund less the cost of SPECIALIZED EQUIPMENT, NEW ITEMS AND RE-CERTIFICATION COSTS, When applicable.

Care is taken to provide accurate specifications. However, Critical areas should be verified by Inspection.

WARRANTY:

FBMS Provides a ONE Year parts and labor Warranty on all reconditioned Testers and 90 Days on Reconditioned tools less all travel and/or Shipping Related Expenses. Unless otherwise specified.

MDNA | AMDA
MMA | ASTM | SAE
ASM

(1) USED MTS Model 506.61, 70 GPM 3,000 PSI Hydraulic Power Supply

SPECIFICATIONS:

Model:	506.61
Serial Number:	210
Flow (GPM):	70
Mfg Date:	3/83
Pressure (PSI):	3,000
Hours:	11,115
Motor:	125 HP/1760 RPM/60HZ
Voltage Requirements (V, Hz, Ph, A):	460, 60, 3, 140

EQUIPPED WITH:

- Water Cooled Heat Exchanger
- Super Charger Pump with 15HP motor

FOB Warren, MI



Frank Bacon Machinery Sales Company, Inc.

4433 East Eight Mile Road • Warren, MI 48090-0886 • (586) 756-4280 • Fax (586) 756-8009 • Toll Free (800) 394-4280
e-mail: sales@frankbacon.com • On The Web: www.frankbacon.com

Stock #: 12235-03

We offer for your consideration, subject to prior sale and conditions stated at the left for immediate acceptance.

Conditions of Sale	Description											
<p>Quotation: Offered for immediate acceptance subject to prior sale or other disposition.</p> <p>Terms: 30% Deposit. Balance due before shipment. NOTE: New items are NON-CANCELABLE and are not subject to return Privilege. We reserve the right to correct typographical errors.</p> <p>Guarantee: Every machine is offered with our customary Machinery Dealers National Association guarantee which provides that if the machine is mechanically unsatisfactory or is misrepresented it may be returned to our Detroit warehouse prepaid and in original condition within 30 days of shipment for full refund of purchase price. This guarantee applies to all machines unless otherwise specified. Care is taken to give accurate specifications from information available. However, critical areas should be verified by inspection.</p> <p>MDNA AMDA MMA ASTM SAE ASM</p>	<p>(1) USED Thermotron, Model F-54-CH-LN2, Environmental Chamber S/N 21-9623, Mfg. 1983</p> <p style="text-align: center;"><u>SPECIFICATIONS:</u></p> <table border="0"> <tr> <td>Inside Dimensions (<i>WxDxH</i>)</td> <td>35" x 44" x 72"</td> </tr> <tr> <td>Temperature Range (<i>Degrees Celsius</i>)</td> <td>-20 to 93 (0° to 200° F)</td> </tr> <tr> <td>Overall Dimensions (<i>WxDxH</i>)</td> <td>49" x 111" x 86"</td> </tr> <tr> <td>Electrical Requirements (<i>V,Hz,Ph</i>)</td> <td>460, 60, 3, 54FLA</td> </tr> <tr> <td>Weight</td> <td>3,100lbs</td> </tr> </table> <p style="text-align: center;"><u>EQUIPPED WITH:</u></p> <ul style="list-style-type: none"> • Circulating fan with 3HP motor • 20" access ports in top and bottom • Viewing Window in Door • Portable dolly to roll chamber into position <p style="text-align: center;">FOB Warren, MI</p>	Inside Dimensions (<i>WxDxH</i>)	35" x 44" x 72"	Temperature Range (<i>Degrees Celsius</i>)	-20 to 93 (0° to 200° F)	Overall Dimensions (<i>WxDxH</i>)	49" x 111" x 86"	Electrical Requirements (<i>V,Hz,Ph</i>)	460, 60, 3, 54FLA	Weight	3,100lbs	
Inside Dimensions (<i>WxDxH</i>)	35" x 44" x 72"											
Temperature Range (<i>Degrees Celsius</i>)	-20 to 93 (0° to 200° F)											
Overall Dimensions (<i>WxDxH</i>)	49" x 111" x 86"											
Electrical Requirements (<i>V,Hz,Ph</i>)	460, 60, 3, 54FLA											
Weight	3,100lbs											