

12122-00	400K Satec/Baldwin BTE
	(1) Reconditioned 400,000 lbf (2,000 kN) Capacity Satec/Baldwin, Model BTE, Hydraulic Tension and
	Compression Testing Machine updated with new Standard Hydraulic Pumping System.
	400K Satec/Baldwin BTE
	SPECIFICATIONS:
	Tension Testing Opening (Less Tooling): 52"
	Compression Testing Opening (Less Tooling): 52"
	Distance Between Columns/Screws: 36"
	Testing Stroke: 12"
	Table Size (W x D): 36" x 36"
	Testing Speed (IPM): 0 – 3
	Crosshead Adjusting Speed (IPM): 12
	Approximate Overall Dimensions:
	Standard Console (W x D x H): 40" x 36" x 38"
	New Servo Hydraulic Console (W x D x H): 36" x 24" x 38"
	Load Frame (W x D x H): 86" × 50" × 156"
	Approximate Weight (lbs): 28,000
	Electrical Requirements (V,Hz,PH): 220/440, 60, 3
	FOB Warren, MI
	Reconditioned/Retrofitted & Certified
	•
	1 Year Parts and Labor Warranty

Guarantee:

Unless otherwise specified, every machine is offered with the standard **MDNA** (*MACHINERY DEALERS NATIONAL ASSOCIATION*) Return privilege to ensure your complete satisfaction. If the machine is un-satisfactory it may be returned to our warehouse, freight prepaid and in the original condition within 30 Days of shipment for a full refund less the cost of SPECIALIZED EQUIPMENT, NEW ITEMS AND RE-CERTIFICATION COSTS, When applicable. Care is taken to provide accurate specifications. However, Critical areas should be verified by Inspection.

MDNA | AMDA | MMA | ASTM | SAE | ASM