



Frank Bacon Machinery Sales Co.

21251 Ryan Road

Warren, MI 48091

586-756-4280 www.frankbacon.com Email: sales@frankbacon.com

| Stock # | DESCRIPTION |
|----------|---|
| 12734-00 | <p data-bbox="293 359 711 386">Newage 3010 Brinell Hardness Tester</p> <p data-bbox="293 401 1313 428">(1) USED Automatic Pneumatic Actuated Dead Weight Brinell Hardness Tester. ASTM E-10</p> <p data-bbox="729 474 1049 543" style="text-align: center;">Newage Model 3010 SPECIFICATIONS:</p> <p data-bbox="293 596 1019 623">Major Brinell Loads(Kgf): 187.5, 250, 500, 750, 1000, 1500, 3000</p> <p data-bbox="293 632 704 659">Standard Vertical Work Height: 9"</p> <p data-bbox="293 667 516 695">Throat Depth: 4.5"</p> <p data-bbox="293 703 850 730">Overall Dimensions (W x D x H): 15" x 26" x 32"</p> <p data-bbox="293 739 496 766">Weight(lbs.): 350</p> <p data-bbox="293 774 824 802">Electrical Requirements(V, Hz, Ph): 115, 60, 1</p> <p data-bbox="293 810 610 837">Air Requirements (psi): 60</p> <p data-bbox="753 884 1023 911" style="text-align: center;">EQUIPPED WITH:</p> <ul data-bbox="293 968 927 1178" style="list-style-type: none">• Simple Pushbutton Automatic Operation• 10mm Diameter Ball Indentor• Flat Anvil• Adjustable Dwell Timer from 12, 30, or 60 Seconds• Pneumatically Actuated Deadweights to Apply Loads• Deadweights <p data-bbox="761 1224 1016 1251" style="text-align: center;">FOB Warren, MI</p> <p data-bbox="469 1260 1308 1287" style="text-align: center;">Cleaned, Serviced & Certified to ASTM Specifications</p> |

Guarantee:

Unless otherwise specified, every machine is offered with the standard **MDNA** (*MACHINERY DEALERS NATIONAL ASSOCIATION*) Return privilege to ensure your complete satisfaction. If the machine is un-satisfactory it may be returned to our warehouse, freight prepaid and in the original condition within 30 Days of shipment for a full refund less the cost of **SPECIALIZED EQUIPMENT, NEW ITEMS AND RE-CERTIFICATION COSTS**, When applicable. Care is taken to provide accurate specifications. However, Critical areas should be verified by Inspection.