

Frank Bacon Machinery Sales Co. 21251 Ryan Road Warren, MI 48091

586-756-4280 www.frankbacon.com Email: sales@frankbacon.com

Stock # DESCRIPTION

12989- 1,125lbf (5kN) Instron 4465

02 (1) Reconditioned 1,125 lbf (5 kN) Capacity Instron, Model 4465, Table Top Precision Two Ball Screw Electro-Mechanical Tension and Compression Testing Machine.

Instron 4465 SPECIFICATIONS:

Tension Testing Opening (Less Tooling): 48"
Compression Testing Opening (Less Tooling): 48"

Distance Between Columns/Screws: 16"

Testing Stroke: 48"

Table Size (W x D): 16" x 6"
Testing Speed (IPM): 0.0004 - 20
Crosshead Adjusting Speed (IPM): 20
Approximate Overall Dimensions:

Load Frame (W x D x H): 35.8" x 27.5" x 62.9"

Approximate Weight (lbs): 360

Electrical Requirements (V,Hz,PH): 120, 60, 1

EQUIPPED WITH:

- ComputerSsystem with Keyboard and Mouse
- 24" LED-Backlit LCD Color Monitor
- Microsoft Windows 10 Professional, Workstation
- MTGenius, Material Testing Software for Data Acquisition (Load, Position & 2 Strain), Analysis and Computer Controlled Testing with Manual.
- MTGenius, Micro Console for Sensor Excitation and Analog/Digital Signal Processing with USB Cable.
- Electronic Material Testing Control System in Custom Cabinet/Desk with PC Controls and Crosshead Jog Controller.
- New Solid State Drive Controller & Electronics for Precision Control of Testing Rates (Load, Position & Strain).
- 5kN Tension & Compression Load Cell

FOB Warren, MI
Reconditioned/Retrofitted & Certified
1 Year Parts and Labor Warranty

*Representative Image

Guarantee: Unless otherwise specified, every machine is offered with the standard **MDNA** (MACHINERY DEALERS NATIONAL ASSOCIATION) Return privilege to ensure your complete satisfaction. If the machine is un-satisfactory it may be returned to our warehouse, freight prepaid and in the original condition within 30 Days of shipment for a full refund less the cost of SPECIALIZED EQUIPMENT, NEW ITEMS AND RE-CERTIFICATION COSTS, When applicable. Care is taken to provide accurate specifications. However, Critical areas should be verified by Inspection.