

Stock

DESCRIPTION

13269-8KIP LDS (Bruel & Kjaer) V875-440 Vibration System with AGREE Chamber (1) USED 8KIP Ling Dynamic Systems (LDS) Vibration System, Model V875-440 Shaker with LDS 01 SPA40/35K Power Amplifier and Thermotron Model F-40-CHMV-25-25-2 AGREE Environmental Chamber. MFG: 2000 Click to View OEM Specifications LDS V875-440 Vibration System **SPECIFICATIONS: Force Rating** (Random): 8,000 lbf (35,585 N) peak (Sine): 8,000 lbf (35,585 N) RMS (Shock): 24,000 lbf (106,752 N) Stroke (Standard): 2" Peak to Peak Frequency Range (Hz): DC to 2,400 Hz Max **Armature Mass:** 69.66 lbs (31.6 KG) Armature Diameter: 440 mm **Acceleration:** (Sine Peak): 110 g (1080 m/s^2) (Random RMS): 75 g (736 m/s^2) Total Weight (lbs): 5,000 lbs Shaker Cooling Airflow: 1200 CFM Voltage Requirements: 480V, 60Hz, 3PH, 61.73 KVA **EQUIPPED WITH:** LDS V875-440 Shaker S/N S5898-001/1 LDS SPAK40/35K 40kVA Power Amplifier S/N S5898-004/1 **Cooling Blower** Thermotron Model F-40-CHMV-25-25-2 AGREE Temperature & Humidity Chamber (S/N: 29944) MFG: 2000 Note: Pulled in Working Condition from Test Facility

FOB Warren, MI Sold in As-Is Condition 30 Day Satisfaction Guaranteed Return Privilege

*Actual Images

Guarantee: Unless otherwise specified, every machine is offered with the standard **MDNA** *(MACHINERY DEALERS NATIONAL ASSOCIATION)* Return privilege to ensure your complete satisfaction. If the machine is un-satisfactory it may be returned to our warehouse, freight prepaid and in the original condition within 30 Days of shipment for a full refund less the cost of SPECIALIZED EQUIPMENT, NEW ITEMS AND RE-CERTIFICATION COSTS, When applicable. Care is taken to

provide accurate specifications. However, Critical areas should be verified by Inspection.