

Frank Bacon Machinery Sales Co. 21251 Ryan Road Warren, MI 48091

586-756-4280 www.frankbacon.com Email: sales@frankbacon.com

Stock # DESCRIPTION

13269- Thermotron VTS-3-6-6-SC/WC Thermal Shock Chamber

07 (1) Used Thermotron, Model ATS-320-DD-10-705 Double Duty Thermal Shock Chamber. S/N 29745

Click to View OEM Brochure

Thermotron Model ATS-320-DD-10-705

SPECIFICATIONS:

Product Carrier Dimensions: 25"W x 15"D x 15"H

Temperature Range:

Hot Chamber: +60°C to +200°C **Cold Chamber:** -73°C to +177°C

Overall Exterior Dimensions: 99"W x 54"D x 100"H

Approximate Weight: 3,800 lbs.

Electrical Requirements: 460V/60Hz/3Ph/121A

MFG Date: 12-8-1999 (Upgraded to New Thermotron 8800 Programmer/Controller)

Performance: To MIL-STD 883, Method 1010.7, MIL-STD 202, Method 107G and Many Other Automotive

and Electronic Thermal Shock Specifications.

Maximum Loading (Mechanical Refrigeration):

-55C to 85C: 120 lbs **-65C to 150C:** 40 lbs

MIL-STD 883 1010.7 Test Load (-65C to 150C): 50lbs

EQUIPPED WITH:

- Stainless Steel Interior
- Refrigeration Service Taps
- Double Duty Transfer Basket (Cold Zone Positioned Between Hot Zones)
- Door Safety Interlocks
- Thermotron 8000 Programmable Touch Screen Controller
- Fully Programmable, Monitor or Control Chamber from any Computer, Tablet or Smart Phone
- Users Manual

FOB Warren, MI
Condition: Excellent

30 Day Satisfaction Guaranteed Return Privilege

* Actual Images

Guarantee: Unless otherwise specified, every machine is offered with the standard MDNA (MACHINERY DEALERS NATIONAL ASSOCIATION) Return privilege to ensure your complete satisfaction. If the machine is un-satisfactory it may be returned to our warehouse, freight prepaid and in the original condition within 30 Days of shipment for a full refund less the cost of SPECIALIZED EQUIPMENT, NEW ITEMS AND RE-CERTIFICATION COSTS, When applicable. Care is taken to provide accurate specifications. However, Critical areas should be verified by Inspection.