

Frank Bacon Machinery Sales Co. 21251 Ryan Road Warren, MI 48091

586-756-4280 www.frankbacon.com Email: sales@frankbacon.com

Stock # DESCRIPTION

13303- Used Lansmont Model 6000 TTV2 Hydraulic Vibration Test System

(1) Lansmont 6000 TTV2 Servo Hydraulic Vibration Test System with Lansmont Hydraulic Power Supply and Vibration Controller

Lansmont 6000 TTV2 Vibration Test System SPECIFICATIONS:

Load Capacity: 2000 lbs

Maximum Stroke: 6" Peak to Peak Frequency Range: 3-200 Hz

Actuator Stall Force: 6160 lbf (27 kN) at 2,500 PSI **Voltage Requirements:** 460V/230V, 60Hz, 3Ph

Cooling Water Requirements: 60 Degrees F at 6 Gal/Min.

Overall Dimensions:

Seismic Base: 49"W x 49"D x 7.75"Thick

Shaker: 60"W x 60"D x 55"H

Hydraulic Pump: 31"W x 31"D x 45"H

EQUIPPED WITH:

- Lansmont TTV2 Controls: Lansmont Vibration Controller Interface and Lansmont Vibration Controller S/N 10754186, Model LAS 200
- Lansmont Water-Cooled Hydraulic Power Supply
- Hydraulic Hoses and System Cables
- Seismic Base with Isolators
- 60" x 60" Aluminum Table with Tapped Grid Area
- General Purpose Accelerometer & Signal Cable

FOB Warren, MI

Serviced by Lansmont on 11/12/24 with Checkout Sheet Available Upon Request

30 Day Satisfaction Guarantee Return Privilege

*Actual Images

Guarantee:

Unless otherwise specified, every machine is offered with the standard MDNA (MACHINERY DEALERS NATIONAL ASSOCIATION) Return privilege to ensure your complete satisfaction. If the machine is un-satisfactory it may be returned to our warehouse, freight prepaid and in the original condition within 30 Days of shipment for a full refund less the cost of SPECIALIZED EQUIPMENT, NEW ITEMS AND RE-CERTIFICATION COSTS, When applicable. Care is taken to provide accurate specifications. However, Critical areas should be verified by Inspection.