



**Frank Bacon Machinery Sales Co.**

**21251 Ryan Road**

**Warren, MI 48091**

**586-756-4280 [www.frankbacon.com](http://www.frankbacon.com) Email: [sales@frankbacon.com](mailto:sales@frankbacon.com)**

Stock #	DESCRIPTION
13255-01JV	<p><b>ESPEC Model BTX-475 Temperature and Humidity Chamber</b> (1) USED ESPEC Model BTX-475 Environmental Temperature and Humidity Chamber. S/N 0637773. Date of Manufacturing May 13th 2015.</p>
<p style="text-align: center;"><b>LINK TO OEM SPECIFICATIONS</b> <b>ESPEC Model BTX-475</b> <b>SPECIFICATIONS:</b></p> <p><b>Lowest temperature:</b> -70°C (-100°F) <b>Highest temperature:</b> 180°C (354°F) <b>Humidity Range:</b> 10 to 95% <b>Approximate Inside Dimensions (W x D x H):</b> 19.6" x 15" x 23.6" <b>Approximate Outside Dimensions (W x D x H):</b> 30.25" x 35" x 75" with table <b>Approximate Chamber Weight (Lbs):</b> 550 <b>Electrical Requirement (V, Hz, Ph.):</b> 208/230, 60, 3, 29A</p>	
<p style="text-align: center;"><b>EQUIPPED WITH:</b></p> <ul style="list-style-type: none"><li>• Rolling Table</li><li>• Space-saving footprint, designed for flush installation to wall</li><li>• Full thermal break around doorframe</li><li>• Easy lift-off service panels, electrical access on left</li><li>• Power cord</li><li>• Humidity models include direct water supply connection for continuous operation</li><li>• 4.0 Cu Ft Workspace Volume</li><li>• 6" Diameter Side Access Ports</li></ul>	
<p style="text-align: center;"><b>FOB Warren, MI</b> <b>30 Day Satisfaction Guaranteed Return Privilege</b></p>	
<p>*Actual Images</p>	

**Guarantee:**

Unless otherwise specified, every machine is offered with the standard **MDNA** (*MACHINERY DEALERS NATIONAL ASSOCIATION*) Return privilege to ensure your complete satisfaction. If the machine is un-satisfactory it may be returned to our warehouse, freight prepaid and in the original condition within 30 Days of shipment for a full refund less the cost of SPECIALIZED EQUIPMENT, NEW ITEMS AND RE-CERTIFICATION COSTS, When applicable. Care is taken to provide accurate specifications. However, Critical areas should be verified by Inspection.